

360 GLIDE™



GAIN CONTROL AND REDUCE FATIGUE

360 GLIDE™ provides reliable, mechanical, automatic positioning of your 360 Y-DROP system that ensures ideal hose position and nitrogen placement.

Your current boom height control system is ideal for bare ground but can struggle to measure above the canopy or through leaves to maintain height. The 360 solution takes control with a simple, reliable sensor rod that mounts to the 360 Y-DROP base and constantly adjusts the 360 Y-DROP base position relative to the ground.





SENSOR TAIL TAKES GUESSWORK OUT OF MEASUREMENT

This tail glides over field terrain reporting the position of the 360 Y-DROP base to your boom-control system and it flexes so it easily handles contours, turns and backing up.

TWO FORMS OF PROTECTION

The height control system is designed to adjust for terrain changes. It doesn't react to rocks, washes and gullies. That's why we include a rugged breakaway system. When an obstruction is hit by the base, the smart system automatically holds its position, then quickly gets back to work controlling boom height.



360 GLIDE uses a mechanical sensor rod to automatically maintain the ideal position of the 360 Y-DROP base. That keeps the delivery hoses in the right angle to deliver nitrogen directly to the base of the corn plant.



Available for John Deere applicators equipped with BoomTrac™ Pro, Hagie, Rogator and CaseIH applicators with Norac UC5.



360 GLIDE plugs into your existing control system and you operate it just like you control your current system. No additional monitors. No elaborate configuration or settings.